

**FURUTECH**  
PURE TRANSMISSION



**AEx**  
オーディオ銘機賞  
Audio Excellence Award 2008

## Speaker Reference III-N1 High End Performance Audio Speaker Cable



Spade Terminal FP-201 (R)

**Speaker Reference III N1-04 · 2 meter**  
**Speaker Reference III N1-06 · 3 meter**

### Features:

- Shielded  $\alpha$  (Alpha)-OCC Conductors eliminate radiated noise
- Formula GC-303 Antimagnetic EMI-Absorbent Modules surround each cable
- High performance beautifully engineered and finished rhodium plated pure copper spades
  - FP-201 (R) Spade terminals nonmagnetic rhodium-plated pure copper (Nonmagnetic rhodium-plated eutectic cast brass FP-202 (R) Banana connectors by request).
- Insulated with high grade PE reducing capacitance and damping vibration
- Results in greater resolution, clarity, powerful dynamics, and an ultra-quiet soundstage in which music develops more fully without artificial upper-frequency "presence region" glare.
- GC-303 allows a deeper, tighter bass to form a solid foundation for the rest of the frequency range, better defining the original recording's venue. Natural, unforced detail reveals nuance and energy for an engaging musical experience.

***$\alpha$  (Alpha) Conductor Is Composed Of Fine OCC Wire Strands  
Treated With Furutech's  $\alpha$  (Alpha) Cryogenic and Demagnetizing Process***

## Here's What The Critics Say

"The Furutech cable sound is easily described as one that completely avoids those peculiar striations that result from highlighting, the providence of certain silver cables that emphasize edge definition for nearly surreal image lock. Such sharp edging then becomes synonymous with etching. It gives a short-lived appearance of exceptional detail - short-lived since such sound is not only unrealistic but fatiguing.

"The Furutech cables patently don't cause this. However, they are exceptionally detailed. I can't help but think that the hexagonal barrel innards [Formula GC-303 Modules] are at least somewhat responsible for this wealth of clearly intelligible inner detail. Rather than throwing detail at you, they throw out inter-note noise. While the end result might seem the same -- more detail -- the way it communicates is very different. Put plainly, the Furutechs never fatigue even at elevated levels yet they do remain ultra resolved."

-- Srajan Ebaen, 6moons.com

## Specifications: Construction and Materials

- 6 bundles of 20-strand  $\alpha$  (Alpha)-OCC Conductor • 0.18mm, 2.7mm diameter
- Insulation: Special Grade PE (Red/White) 5.1mm diameter
- Cable Lay: Two twisted cores together with cotton yarn
- Sheath: Two layers flexible PVC (Purple/Blue) 14.3±0.2mm diameter
- Shield: Special EMI- and noise-absorbent Formula GC-303 module
- Jacket: Nylon yarn braid approx. 15.3±0.2mm
- Connectors: Spade Terminal [FP-201 (R)] or Banana Connectors [FP-202 (R)]

| Electrical Properties of Cable |                     | Test Method       |
|--------------------------------|---------------------|-------------------|
| Max. Conductor Resistance      | 6.2 $\Omega$ /km    | JISC3005 6 20°C   |
| Min. Insulation Resistance     | 1000 M $\Omega$ -km | JISC3005 9.1 20°C |
| Dielectric Strength            | AC. 1000 V/1 min.   | JISC3005 8        |
| Electrostatic Capacitance      | Approx 50 PF/m      | at 1 KHz          |

*All metallic parts are treated with the*

*\*FURUTECH  $\alpha$  (Alpha) Process (Super Cryogenic & Demagnetizing Treatment.)*

**FURUTECH CO., LTD.**  
[service@furutech.com](mailto:service@furutech.com)

***Make A More Powerful Connection With Furutech!***